

SKYLIGHT MAINTENANCE INSTRUCTIONS

Skylight Maintenance

A scheduled preventative maintenance program should be followed. This maintenance program will vary in frequency based on environmental conditions of the jobsite and should be determined by the building maintenance staff at the site.

Cleaning Skylight Lenses

- When cleaning the plastic skylight lenses use only water or water with a mild soap. A pressure washer or soft rag should be used to minimize scratching the plastic lens.
 - When using a pressure washer, maintain an appropriate distance from the skylight based on psi rating of pressure washer. Damage may occur to skylight otherwise.
 - A 40-degree nozzle or wider should be used
 - Keep moving pressure washer wand across skylight, do not concentrate on one location too long.
- Never use ammonia, alcohol, aromatic or petroleum-based products to clean the plastic lenses. This will cause deterioration and cracking of the lens and will void the warranty.

DELIVER TO END USER AFTER INSTALLATION IS COMPLETED

Sunoptics recommends professional installation of the skylights by a competent licensed contractor. Sunoptics is not an insurer of, or for any Contractor/Installer of its products and has no control over the installation process. Therefore Sunoptics is to be held completely harmless from any litigation arising from installation mishap, regardless of cause, or severity.

Sunoptics recommends using only reputable contractors that are experienced licensed and bonded. This is a guide for typical installation, your specific installation techniques may vary. You are responsible for complying with local building codes. Please consult an engineer regarding structural modifications and support for the system